



Resistance Alloys (India) Ltd.

RAIL[®] -2 Wire

RAIL[®] -2 Wire is an Iron-chromium-aluminium alloy, mainly composed of high purity electrolytic iron, low carbon ferro-chrome and high purity aluminum and can withstand temperature up to 1100°C

RAIL[®] -2 Wire is primarily used for making element for electric heater/stove.

Size range : SWG 20-24 / 0.90 – 055 MM



is the Regd. Trade Mark of Resistance Alloys (India) Ltd.

This information is meant for user's guidance only. It is being published to the best of our knowledge and is subject to change as additional knowledge and experience is gained. It should not be construed as a warranty or representation implying any legal responsibility on us.

Regd. Office & Factory :

Village Raihati
Trilochan Mahadev
Tehsil : Kerakat
Dist : Jaunpur, U. P.
Pin : 222 102
Tel : 05450-233 333
E-mail : railfact@railind.com

Marketing Division :

1-A Chemox House, 1st Floor
7 Barrack Road
Mumbai - 400 020
Tel : 022 - 2206 7076
2203 6570 / 71
Fax : 022 - 2208 0169
E-mail : rail@railind.com

Kolkata Branch :

10 B Rameshwara Apts
19A Sarat Bose Road
Kolkata - 700 020
Tel : 033-2235 9968
Fax : 033-2215 4535
E-mail : railkol@railind.com

Delhi Branch :

Kundan Mansion, 2nd Floor
1783 Electrical Market
Chandni Chowk
Delhi - 110 006
Tel : 011- 2386 1070
Telefax : 011- 2386 3056
E-mail : raildel@railind.com

Web : www.railind.com